


DIAGONAL BAR DETAILS

NOTES

1. APPLICABLE TO SLIP FORM CONSTRUCTION METHOD ONLY.
2. FOR BARRIER TYPES 1, 2, 3 AND BARRIERS CONSTRUCTED ON EXISTING RIGID PAVEMENT.
3. DIAGONAL NO.4 BARS SHALL BE ASTM A 615 GRADE 60.
4. ALL REINFORCEMENT BARS INCLUDING ENDS AND TIES SHALL BE EPOXY COATED.
5. REFER TO STANDARDS FOR SPACING OF VERTICAL AND HORIZONTAL REINFORCEMENT.

SPECIFICATION 604	CATEGORY CODE ITEMS
APPROVED	<i>Kirk G. McCall</i> DIRECTOR - OFFICE OF HIGHWAY DEVELOPMENT
	APPROVAL • SHA REVISIONS
	APPROVAL 3-1-01
	REVISED 10-1-01
	REVISED
	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION
	APPROVAL 3-28-01
	REVISED
	REVISED

Maryland Department of Transportation
STATE HIGHWAY ADMINISTRATION
 STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES
DIAGONAL BAR FOR SLIP FORMED 34 INCH
OR 42 INCH F SHAPE SINGLE FACE
CONCRETE TRAFFIC BARRIER

STANDARD NO. MD 648.49